

COMPAL CONFIDENTIAL

MODEL NAME : NCL01
PCB NO : LA-5472P (DAA00001I00)

E2 Rothschild DSC
rPGA Arrandale +
FCBGA PCH IBEXPEAK-M
+ N10M-NS-S
2010-01-20
REV : 1.0(A00)
@ : Nopop Component

MB Type	BOM P/N	PCMCIA	Express	TCM		TPM		7@	8@	ATG	BOM CONFIG
		1@	2@	W(3@)	W/O(4@)	W(5@)	W/O(6@)			9@	
EXPRESS CARD ,Enble TPM ,Disable TCM	43177831L01		*		*	*					2@,4@,5@
EXPRESS CARD ,Disable TPM ,Enble TCM	43177831L02		*	*			*				2@,3@,6@
EXPRESS CARD ,Disable TPM ,Disable TCM	43177831L03		*		*		*				2@,4@,6@
PCMCIA CARD ,Enble TPM ,Disable TCM	43177831L04	*			*	*					1@,4@,5@
PCMCIA CARD ,Disable TPM ,Enble TCM	43177831L05	*		*			*				1@,3@,6@
PCMCIA CARD ,Disable TPM ,Disable TCM	43177831L06	*			*		*				1@,4@,6@

MB PCB	
Part Number	Description
DAA0A00100	PCB NCL01 LA-5472P LS-5471P/5473P/5574P

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.



DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.

Title

Cover Sheet

Size

Document Number

LA-5472P

Rev

A00

Date

Wednesday, January 20, 2010


Sheet

1

of

66

Block Diagram
Compal confidential
Model : NCL01



POWER STATES

Signal State	SLP S3#	SLP S4#	SLP S5#	S4 STATE#	SLP M#	ALWAYS PLANE	M PLANE	SUS PLANE	RUN PLANE	CLOCKS
S0 (Full ON) / M0	HIGH	HIGH	HIGH	HIGH	HIGH	ON	ON	ON	ON	ON
S3 (Suspend to RAM) / M1	LOW	HIGH	HIGH	HIGH	HIGH	ON	ON	ON	OFF	OFF
S4 (Suspend to DISK) / M1	LOW	LOW	HIGH	LOW	HIGH	ON	ON	OFF	OFF	OFF
S5 (SOFT OFF) / M1	LOW	LOW	LOW	LOW	HIGH	ON	ON	OFF	OFF	OFF
S3 (Suspend to RAM) / M-OFF	LOW	HIGH	HIGH	HIGH	LOW	ON	OFF	ON	OFF	OFF
S4 (Suspend to DISK) / M-OFF	LOW	LOW	HIGH	LOW	LOW	ON	OFF	OFF	OFF	OFF
S5 (SOFT OFF) / M-OFF	LOW	LOW	LOW	LOW	LOW	ON	OFF	OFF	OFF	OFF

PM TABLE

power plane State	+15V_ALW +5V_ALW +3.3V_ALW_PCH +3.3V_RTC_LDO	+3.3V_SUS +1.5V_MEM	+5V_RUN +3.3V_RUN +1.8V_RUN +1.5V_RUN +0.75V_DDR_VTT +VCC_CORE +1.05V_RUN_VTT +1.05V_RUN	+3.3V_M +1.05V_M	+3.3V_M +1.05V_M (M-OFF)
S0	ON	ON	ON	ON	ON
S3	ON	ON	OFF	ON	OFF
S5 S4/AC	ON	OFF	OFF	ON	OFF
S5 S4/AC don't exist	OFF	OFF	OFF	OFF	OFF

PCH	USB PORT#	DESTINATION
	0	JUSB1 (Ext Right Side Top)
	1	JUSB1 (Ext Right Side Bottom)
	2	JESA1 (Ext Left Side Top)
	3	JESA1 (Ext Left Side Bottom)
	4	WLAN
	5	WWAN
	6	Bluetooth
	7	USH->BIO
	8	DOCKING
	9	DOCKING
	10	Express card
	11	Camera
	12	none
	13	JMINI3(PCIE/BKT CARD)


PCI EXPRESS	DESTINATION
Lane 1	MINI CARD-1 WWAN
Lane 2	MINI CARD-2 WLAN
Lane 3	PCMCIA
Lane 4	EXPRESS CARD
Lane 5	MINI CARD-3 PCIE/BKT
Lane 6	10/100/1G LAN
Lane 7	None
Lane 8	None

DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.

Title	Index and Config.		
Size	Document Number	LA-5472P	Rev A00
Date:	Wednesday, January 20, 2010	Sheet 3	of 66



PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL") THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.





PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.



DELL CONFIDENTIAL/PROPRIETARY		
Compal Electronics, Inc.		
Title Power Rail		
Size	Document Number LA-5472P	Rev A00
Date	Wednesday, January 20, 2010	Sheet 4 of 66




+CLK_VDD_IO CAN BE RANGE FROM 1.05V TO 3V



REF_O/CPU_SEL

PIN	30	CPU0	CPU1
1	(0.7~1.5v)	100MHz	100MHz
0	(DEFAULT)	133MHz	133MHz






DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.

Clock Generator			
Title	LA-5472P		
Size	Document Number	Rev	A00
Date:	Wednesday, January 20, 2010	Sheet	6 of 66

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.




DELL CONFIDENTIAL/PROPRIETARY



Compal Electronics, Inc.

Title			
Arrandale (1/6)			
LA-5472P			
Date:	Wednesday, January 20, 2010	Sheet	7 of 66


PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL") THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.



DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.			
Title			
Arrandale (2/6)			
LA-5472P			
Size	Document Number	Rev A00	
Date:	Wednesday, January 20, 2010	Sheet	8 of 66


PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL") THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.



DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.

Title			
Arrandale (3/6)			
Size	Document Number		Rev
	LA-5472P		A00
Date:	Wednesday, January 20, 2010	Sheet 9 of 66	



REV1.0

TYCO_CALPELLA_AUBURNDAL

PCI-Express Configuration Select	
CFG0	1 : Single PEG 0 : Bifurcation enable

PCI-Express Static Lane Reversal	
CFG3	1 : Normal Operation 0 : Lane Number Reversed 15->0, 14->1 ...




Display Port Presence	
CFG4	1 : Disabled; No Physical Display Port attached to Embedded Display Port 0 : Enabled; An external Display Port device is connected to the Embedded Display Port

DELL CONFIDENTIAL/PROPRIETARY



Compal Electronics, Inc.			
Title			
Arrandale (4/6)			
Size	Document Number	Rev	
	LA-5472P	A00	
Date:	Wednesday, January 20, 2010	Sheet	10 of 66

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL
TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT
BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION,
NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD
PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.




POWER

CPU VIDS

SENSE LINES

REV1.0
TYCO_CALPELLA_AUBURNDAL




Place R1116 and R1117 near CPU
Route VCCSENSE and VSSSENSE trace at
27.4 ohms, 7 mils spacing

DELL CONFIDENTIAL/PROPRIETARY



Compal Electronics, Inc.			
Title			
Arrandale (5/6)			
Size			
Document Number			
LA-5472P			
Date			
Wednesday, January 20, 2010			
Sheet			
11 of 66			
Rev			
A00			

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.



GRAPHICS

POWER

PEG & DMI

SENSE LINES

GRAPHICS VIDS


DDR3 - 1.5V RAILS

1.1V

1.8V

REV1.0
TYCO_CALPELLA_AUBURNDALE

+1.5V_CPU_VDDQ Source



3A

600mA

REV1.0
TYCO_CALPELLA_AUBURNDALE

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.




DELL CONFIDENTIAL/PROPRIETARY




Compal Electronics, Inc.

Arrandale (6/6)

Title			
Arrandale (6/6)			
Size	Document Number		Rev
	LA-5472P		A00
Date:	Wednesday, January 20, 2010	Sheet	12 of 66










Note:
Check voltage tolerance of
VREF_DQ at the DIMM socket




PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.



ME_CLR1	TPM setting
Shunt	Clear ME RTC Registers
Open	Keep ME RTC Registers




		PCH JTAG Enable		PCH JTAG Disable		Production
PCH Pin	Ref.	ES1	ES2	ES1	ES2	All
TDO	R806	No Stuff	200 ohm	No Stuff	No Stuff	200 ohm
	R1315	No Stuff	100 ohm	No Stuff	No Stuff	100 ohm
TMS	R807	200 ohm	200 ohm	No Stuff	No Stuff	200 ohm
	R1281	100 ohm	100 ohm	No Stuff	No Stuff	100 ohm
TDI	R805	200 ohm	200 ohm	20K ohm	No Stuff	200 ohm
	R1282	100 ohm	100 ohm	10K ohm	No Stuff	100 ohm
TCK	R804	4.7K ohm	4.7K ohm	4.7K ohm	4.7K ohm	51 ohm
TRST#	R808	20K ohm	No Stuff	No Stuff	No Stuff	No Stuff




DELL CONFIDENTIAL/PROPRIETARY



Compal Electronics, Inc.			
Title		PCH (1/8)	
Size	Document Number	Rev	
	LA-5472P	A00	
Date:	Wednesday, January 20, 2010	Sheet	15 of 66






Intel WW18 Strapping option


PORT	STRAP	ENABLE	DISABLE
LVDS	L_DDC_DATA	PU to 3.3V through 2.2Kohm	NC
PORT B	SDVO_CTRLDATA	PU to 3.3V through 2.2Kohm	NC
PORT B	DDPC_CTRLDATA	PU to 3.3V through 2.2Kohm	NC
PORT B	DDPD_CTRLDATA	PU to 3.3V through 2.2Kohm	NC
eDP on CPU	CFG[4] (at CPU)	PD to GND through 3.3Kohm	NC




Intel request DDPB can not support eDP



DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.			
Title			
PCH (3/8)			
Size	Document Number	Rev A00	
LA-5472P			
Date:	Wednesday, January 20, 2010	Sheet	17 of 66





	TPM_ID0	TPM_ID1
China TPM	0	0
No TPM, No China TPM	0	1
Reserved	1	0
TPM	1	1




DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.

Title: **PCH (5/8)**

Size	Document Number	Rev
	LA-5472P	A00
Date:	Wednesday, January 20, 2010	Sheet 19 of 66





PCH Power Rail Table		
Voltage Rail	Voltage	SO Iccmax Current (A)
V_CPU_IO	1.1/1.05	< 1 (mA)
V5REF	5	< 1 (mA)
V5REF_Sus	5	< 1 (mA)
Vcc3_3	3.3	0.357
VccAClk	1.1	0.052
VccADAC	3.3	0.069
VccADPLLA	1.1	0.068
VccADPLLB	1.1	0.069
Vccap11EXP	1.1	0.04
VccCore	1.1	1.432
VccDMI	1.1	0.058
VccDMI	1.1	0.061
VccFDIPLL	1.1	0.037
VccIO	1.1	3.062
VccLAN	1.1	0.32
VccME	1.1	1.849
VccME3_3	3.3	0.085
VccpNAND	1.8	0.156
VccRTC	3.3	2 (mA)
VccSATAPLL	1.1	0.031
VccSus3_3	3.3	0.163
VccSusHDA	3.3	0.006
VccVRM	1.8 / 1.5	0.196
VccALVDS	3.3	< 1 (mA)
VccTX_LVDS	1.8	0.059

DELL CONFIDENTIAL/PROPRIETARY



Compal Electronics, Inc.

Title		
PCH (6/8)		
Size	Document Number	Rev A00
LA-5472P		
Date:	Wednesday, January 20, 2010	Sheet 20 of 66




DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.

Title PCH (8/8)

Size Document Number LA-5472P Rev A00

Date: Wednesday, January 20, 2010 Sheet 22 of 66





DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.

FAN & Thermal Sensor

LA-5472P

Date: Wednesday, January 20, 2010 Sheet 23 of 66



PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL") THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.

DELL CONFIDENTIAL/PROPRIETARY



Compal Electronics, Inc.			
Title			
DPB AUX SW for DOCK			
Size	Document Number	Rev	
	LA-5472P	A00	
Date:	Wednesday, January 20, 2010	Sheet	25 of 66

B



3



Diagram illustrating a circuit for a back-up plan, showing a +3.3V_RUN supply connected to a series of resistors and capacitors. The components are labeled:


- P1 OC1 @R1542
- P1 OC0 @R1543
- P2 OC1 @R1544
- P2 OC0 @R1546

Each component is connected to a 4.7K_0402 5%-D resistor. The resistors are connected in series, with the final resistor connected to ground.



Title			
Display port			
Size	Document Number		Rev
	LA-5472P		A00
Date:	Wednesday, January 20, 2010		Sheet 26 of 66

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL") THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.



Pin configuration diagram for the PIV712-AZLEX_TQFN32_6X3-D package. The diagram shows a top-down view of the package with pins numbered 1 through 32. Signals are connected to specific pins:




- GPU_CRT_VSYNC (pins 1, 4)
- GPU_CRT_HSYNC (pins 2, 5)
- GPU_CRT_RED (pins 3, 6)
- GPU_CRT_GRN (pins 4, 7)
- GPU_CRT_BLU (pins 5, 8)
- CRT_SWITCH (pin 8)
- GPU_CRT_DAT_DDC (pins 9, 10)
- GPU_CRT_CLK_DDC (pins 9, 10)
- CRT_SWITCH (pin 30)
- GND (pins 3, 11, 28, 31, 33)
- GPAD (pin 33)
- VDD (pins 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33)
- VSYNC_BUF (pin 27)
- HSYNC_BUF (pin 25)
- RED_CRT (pin 22)
- GREEN_CRT (pin 21)
- BLUE_CRT (pin 18)
- DAT_DDC2_CRT (pin 12)
- CLK_DDC2_CRT (pin 14)
- VSYNC_DOCK (pin 26)
- HSYNC_DOCK (pin 24)
- RED_DOCK (pin 19)
- GREEN_DOCK (pin 21)
- BLUE_DOCK (pin 17)
- DAT_DDC2_DOCK (pin 15)
- CLK_DDC2_DOCK (pin 12)

The schematic shows a 3.3V rail (labeled +3.3V RUN) connected to a series of decoupling capacitors. From left to right, the components are:






- A 100µ 0805 10V A-Z-D capacitor.
- A 0.1µ 0402 16V A-Z-D capacitor, labeled C259.
- A 0.1µ 0402 16V A-Z-D capacitor, labeled C260.
- A 0.1µ 0402 16V A-Z-D capacitor, labeled C261.
- A 0.1µ 0402 16V A-Z-D capacitor, labeled C262.
- A 0.1µ 0402 16V A-Z-D capacitor, labeled C263.
- A 0.1µ 0402 16V A-Z-D capacitor, labeled C264.

Each capacitor is connected between the 3.3V rail and a common ground plane, represented by a series of red triangles at the bottom.

Rev
A00






Free Fall Sensor




PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL") THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.




Compal Electronics, Inc.			
ODD/HDD CONNECTOR			
LA-5472P			
Date: Wednesday, January 20, 2010	Sheet 28 of 66	Rev A00	66

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.








C710, C713 as close as possible to U94



MFIO Pin Assignment Table

MFIO	SD8	XD	MS8
00	WP	D7	BS
01	D1	D6	-
02	D0	D5	D1
03	D7	D4	-
04	D6	D3	D5
05	CLK	D2	D0
06	-	D1	-
07	D5	D0	D4
08	CMD	WP#	D2
09	D4	WE#	D6
10	D3	ALE	D3
11	D2	CLE	-
12	-	CE#	-
13	-	RE#	D7
14	-	R/B#	CLK

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL") THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.




DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.



Title			R5U242 (1/2)		
Size	Document Number	Rev			A00
Date	Wednesday, January 20, 2010	Sheet	33	of	66



Power Control for Mini card1

Power Control for Mini card2

Power Control for Mini card3

DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.

PCIE PWR


LA-5472P

Wednesday, January 20, 2010

Sheet 35 of 66

Rev A00

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.



Power Control for Mini card1

Power Control for Mini card2

Power Control for Mini card3

DELL CONFIDENTIAL/PROPRIETARY


Compal Electronics, Inc.

PCIE PWR

LA-5472P

Rev A00

Proprietary Note: This sheet of engineering drawing and specifications contains confidential trade secret and other proprietary information of Dell Inc. ("Dell"). This document may not be transferred or copied without the express written authorization of Dell. In addition, neither this sheet nor the information it contains may be used by or disclosed to any third party without Dell's express written consent.



Power Control for Mini card1

Power Control for Mini card2

Power Control for Mini card3

DELL CONFIDENTIAL/PROPRIETARY


Compal Electronics, Inc.

PCIE PWR

LA-5472P

Rev A00

Proprietary Note: This sheet of engineering drawing and specifications contains confidential trade secret and other proprietary information of Dell Inc. ("Dell"). This document may not be transferred or copied without the express written authorization of Dell. In addition, neither this sheet nor the information it contains may be used by or disclosed to any third party without Dell's express written consent.



Power Control for Mini card1

Power Control for Mini card2

Power Control for Mini card3

DELL CONFIDENTIAL/PROPRIETARY


Compal Electronics, Inc.

PCIE PWR

LA-5472P

Rev A00

Proprietary Note: This sheet of engineering drawing and specifications contains confidential trade secret and other proprietary information of Dell Inc. ("Dell"). This document may not be transferred or copied without the express written authorization of Dell. In addition, neither this sheet nor the information it contains may be used by or disclosed to any third party without Dell's express written consent.



Power Control for Mini card1

Power Control for Mini card2

Power Control for Mini card3

DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.

PCIE PWR

LA-5472P

Rev A00

Proprietary Note: This sheet of engineering drawing and specifications contains confidential trade secret and other proprietary information of Dell Inc. ("Dell"). This document may not be transferred or copied without the express written authorization of Dell. In addition, neither this sheet nor the information it contains may be used by or disclosed to any third party without Dell's express written consent.

Power Control for Mini card1

Power Control for Mini card2

Power Control for Mini card3

DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.

PCIE PWR

LA-5472P

Rev A00

Proprietary Note: This sheet of engineering drawing and specifications contains confidential trade secret and other proprietary information of Dell Inc. ("Dell"). This document may not be transferred or copied without the express written authorization of Dell. In addition, neither this sheet nor the information it contains may be used by or disclosed to any third party without Dell's express written consent.

Power Control for Mini card1

Power Control for Mini card2

Power Control for Mini card3

DELL CONFIDENTIAL/PROPRIETARY
Compal Electronics, Inc.

PCIE PWR

LA-5472P

Wednesday, January 20, 2010

Sheet 35 of 66

Rev A00

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.

Power Control for Mini card1

Power Control for Mini card2

Power Control for Mini card3

DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.

PCIE PWR

LA-5472P

Rev A00

Proprietary Note: This sheet of engineering drawing and specifications contains confidential trade secret and other proprietary information of Dell Inc. ("Dell"). This document may not be transferred or copied without the express written authorization of Dell. In addition, neither this sheet nor the information it contains may be used by or disclosed to any third party without Dell's express written consent.

Power Control for Mini card1

Power Control for Mini card2

Power Control for Mini card3

DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.

PCIE PWR

LA-5472P


Wednesday, January 20, 2010

Sheet 35 of 66

Rev A00


PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.

Mini WWAN




PWR Rail	Voltage Tolerance	Primary Power		Aux Power
		Peak	Normal	Normal
+3.3V	+9%	1000	750	
+3.3Vaux	+9%	330	250	250 (Wake enable) 5 (Not wake enable)
+1.5V	+5%	500	375	NA


SIM Card




Reserved for test



Mini WLAN




PCIE/BKT Card




PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.

DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.			
Mini Card			
Title	Document Number	Rev	A00
	LA-5472P		
Date: Wednesday, January 20, 2010	Sheet 36	of	66






	VGA_ID_UMA	VGA_ID_DISC
Discrete	0	1
UMA	1	0
SG	1	1

DELL CONFIDENTIAL/PROPRIETARY



Compal Electronics, Inc.			
Title ECE5028			
Size	Document Number LA-5472P	Rev A00	
Date	Wednesday, January 20, 2010	Sheet	39 of 66

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSMITTED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.



DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.

File: **EMC5045**

Size: **Document Number**

LA-5472P

Date: Wednesday, January 20, 2010

Sheet: 40 of 66

Rev: A00

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSMITTED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.

Figure 1: Pin connections for the HRS_FH12-16S-0P5SH(55)-D module. The diagram shows a 16-pin connector (J1P1) with pins 1 through 16. Pin 1 is labeled '1C' and pin 16 is labeled '16C'. Pin 17 is labeled 'G1' and pin 18 is labeled 'G2'. The module is labeled 'HRS_FH12-16S-0P5SH(55)-D'. The connections are: Pin 1: +3.3V_ALW; Pin 2: 0.1uF, 0402, 16V4Z-D; Pin 3: 40 BC_CLK_ECE1077; Pin 4: 40 BC_DAT_ECE1077; Pin 5: 40 BC_INT#_ECE1077; Pin 6: +3.3V_ALW; Pin 7: +3.3V_RUN; Pin 8: TP_CLK; Pin 9: TP_DATA; Pin 10: +5V_RUN; Pin 11: +5V_ALW; Pin 12: 40 KYBRD_BKLT_PWM; Pin 13: KYBRD_BKLT_PWM; Pin 14: 39 TP_DET#; Pin 15: TP_DET#; Pin 16: +5V_RUN; Pin 17: 0.1uF, 0402, 16V4Z-D; Pin 18: +5V_ALW. A note says 'Place close to J1P1. 5, 6'. A note says 'Place close to J1P1. 5, 6'. A note says 'Place close to J1P1. 5, 6'.



The schematic diagram illustrates the electrical connection between a BT module and the E&T_3703-E12N-03R module. The BT module is represented by a blue box on the left with pins 1 through 14. The E&T module is represented by a blue box on the right with pins 1 through 14, labeled G1, G2, and G3. The connections are as follows:

- Pin 1 (BT DET#):** Connected to the E&T module's pin 1 (G1).
- Pin 36 (COEX1_BT_ACTIVE):** Connected to the E&T module's pin 2 (G2).
- Pin 43 (BT ACTIVE):** Connected to the E&T module's pin 3 (G3).
- Pin 39 (BT RADIO DIS#):** Connected to the E&T module's pin 4 (G4).
- Pin 36 (COEX2_WLAN_ACTIVE):** Connected to the E&T module's pin 5 (G5).
- Pin 18 (USBP6-):** Connected to the E&T module's pin 6 (G6).
- Pin 18 (USBP6+):** Connected to the E&T module's pin 7 (G7).
- Pin 10 (BT DET#):** Connected to the E&T module's pin 8 (G8).
- Pin 11 (BT RADIO DIS#):** Connected to the E&T module's pin 9 (G9).
- Pin 12 (BT DET#):** Connected to the E&T module's pin 10 (G10).
- Pin 13 (BT RADIO DIS#):** Connected to the E&T module's pin 11 (G11).
- Pin 14 (BT DET#):** Connected to the E&T module's pin 12 (G12).
- Pin 15 (BT RADIO DIS#):** Connected to the E&T module's pin 13 (G13).
- Pin 16 (BT DET#):** Connected to the E&T module's pin 14 (G14).

The E&T module is labeled "E&T_3703-E12N-03R". The BT module is labeled "BT". The connections are labeled with pin numbers and component values: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, 101, 102, 103, 104, 105, 106, 107, 108, 109, 110, 111, 112, 113, 114, 115, 116, 117, 118, 119, 120, 121, 122, 123, 124, 125, 126, 127, 128, 129, 130, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 141, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156, 157, 158, 159, 160, 161, 162, 163, 164, 165, 166, 167, 168, 169, 170, 171, 172, 173, 174, 175, 176, 177, 178, 179, 180, 181, 182, 183, 184, 185, 186, 187, 188, 189, 190, 191, 192, 193, 194, 195, 196, 197, 198, 199, 200, 201, 202, 203, 204, 205, 206, 207, 208, 209, 210, 211, 212, 213, 214, 215, 216, 217, 218, 219, 220, 221, 222, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 233, 234, 235, 236, 237, 238, 239, 240, 241, 242, 243, 244, 245, 246, 247, 248, 249, 250, 251, 252, 253, 254, 255, 256, 257, 258, 259, 260, 261, 262, 263, 264, 265, 266, 267, 268, 269, 270, 271, 272, 273, 274, 275, 276, 277, 278, 279, 280, 281, 282, 283, 284, 285, 286, 287, 288, 289, 290, 291, 292, 293, 294, 295, 296, 297, 298, 299, 300, 301, 302, 303, 304, 305, 306, 307, 308, 309, 310, 311, 312, 313, 314, 315, 316, 317, 318, 319, 320, 321, 322, 323, 324, 325, 326, 327, 328, 329, 330, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 350, 351, 352, 353, 354, 355, 356, 357, 358, 359, 360, 361, 362, 363, 364, 365, 366, 367, 368, 369, 370, 371, 372, 373, 374, 375, 376, 377, 378, 379, 380, 381, 382, 383, 384, 385, 386, 387, 388, 389, 390, 391, 392, 393, 394, 395, 396, 397, 398, 399, 400, 401, 402, 403, 404, 405, 406, 407, 408, 409, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 420, 421, 422, 423, 424, 425, 426, 427, 428, 429, 430, 431, 432, 433, 434, 435, 436, 437, 438, 439, 440, 441, 442, 443, 444, 445, 446, 447, 448, 449, 450, 451, 452, 453, 454, 455, 456, 457, 458, 459, 460, 461, 462, 463, 464, 465, 466, 467, 468, 469, 470, 471, 472, 473, 474, 475, 476, 477, 478, 479, 480, 481, 482, 483, 484, 485, 486, 487, 488, 489, 490, 491, 492, 493, 494, 495, 496, 497, 498, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 547, 548, 549, 550, 551, 552, 553, 554, 555, 556, 557, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 578, 579, 580, 581, 582, 583, 584, 585, 586, 587, 588, 589, 590, 591, 592, 593, 594, 595, 596, 597, 598, 599, 600, 601, 602, 603, 604, 605, 606, 607, 608, 609, 610, 611, 612, 613, 614, 615, 616, 617, 618, 619, 620, 621, 622, 623, 624, 625, 626, 627, 628, 629, 630, 631, 632, 633, 634, 635, 636, 637, 638, 639, 640, 641, 642, 643, 644, 645, 646, 647, 648, 649, 650, 651, 652, 653, 654, 655, 656, 657, 658, 659, 660, 661, 662, 663, 664, 665, 666, 667, 668, 669, 670, 671, 672, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 685, 686, 687, 688, 689, 690, 691, 692, 693, 694, 695, 696, 697, 698, 699, 700, 701, 702

Power Switch for debug

40.43 POWER_SW#_MB << POWER_SW# MB

@C684
100P_0402_50V&J-D

PWRSW1
@SHORT PADS-D
Place on Top

PWRSW2
@SHORT PADS-D
Place on Bottom

Part Number	Description
DC28A000800	FAN SET DAQ20 DC5V AB7405HB-HB3 ADDA

Part Number	Description
PK230003Q0L	SPK PACK ZJX 2.0W 4 OHM FG

Part Number	Description
SP070007V0L	S SOCKET TYCO 1770551-1 10P H5.9 SMART

Part Number	Description
DC000001Q0L	PCMCIA TYCO 1759096-1

Part Number	Description
DC02000CS0L	H-CONN SET ZGX MB-MDC

Part Number	Description
DC02000840L	H-CONN SET ZJX MB-B/T-TP-FP

Part Number	Description
DC020003Y0L	H-CONN SET ZJX MB-LCD 14 WXGA+(-1ch)

Part Number	Description
DC02000870L	H-CONN SET ZJX MB-LCD 14 WXGA+ (-2ch)


Part Number	Description
GC20323MX00	BATT CR2032 3V 220MAH MAXELL




Title			
Touch PAD/Int KB/LID			
Size	Document Number		Rev
	LA-5472P		A00
Date:	Wednesday, January 20, 2010	Sheet 41 of 66	

DC/DC Interface


+3.3V_ALW_PCH Source




+3.3V_SUS Source




+3.3VM Source




Discharg Circuit




Discharg Circuit




+5VRUN Source




+3.3V_RUN Source



+1.5V_RUN Source



+1.05V_RUN Source



PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.

DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.

POWER CONTROL

LA-5472P







Size

Document Number




Wednesday, January 20, 2010

Sheet 42 of 66



Rev A00



LED Circuit Control Table		
	SYS_LED_MASK#	LID_CL#
Mask All LEDs (Sniffer Function)	0	X
Mask Base MB LEDs (Lid Closed)	1	0
Do not Mask LEDs (Lid Opened)	1	1



PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL EMC. ("DELL") THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.



DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.


+DCIN

LA-5472P

Date: Wednesday, January 20, 2010 Sheet 44 of 66


THIS SHEET OF ENGINEERING DRAWING IS THE PROPRIETARY PROPERTY OF COMPAL ELECTRONICS, INC. AND CONTAINS CONFIDENTIAL AND TRADE SECRET INFORMATION. THIS SHEET MAY NOT BE TRANSFERRED FROM THE CUSTODY OF THE COMPETENT DIVISION OF R&D DEPARTMENT EXCEPT AS AUTHORIZED BY COMPAL ELECTRONICS, INC. NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT PRIOR WRITTEN CONSENT OF COMPAL ELECTRONICS, INC.

+1.5V_SUS_P (TPS51318)



1.5 Volt +/-5%
Thermal Design Current : 7.876A
Peak current : 11.251A
OCP_MIN : 13.501A

+1.5V_SUS_P (VT356)



	PR61
UMA	5.9K
DSC	6.49K

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.

THIS SHEET OF ENGINEERING DRAWING IS THE PROPRIETARY PROPERTY OF COMPAL ELECTRONICS, INC. AND CONTAINS CONFIDENTIAL AND TRADE SECRET INFORMATION. THIS SHEET MAY NOT BE TRANSFERRED FROM THE CUSTODY OF THE COMPETENT DIVISION OF R&D DEPARTMENT EXCEPT AS AUTHORIZED BY COMPAL ELECTRONICS, INC. NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS




DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.


+1.5V MEM

Title	LA-5472P	Rev	A00
Size	Document Number		
Date	Wednesday, January 20, 2010	Sheet	46 of 66

5V_DDR_VTT



0.75Volt +/-5%
Thermal Design Current: 0.525A
Peak current: 0.750A
OCP mini: 0.900A




+0.75V_DDR_VT/+1.8V_RUN


Date: Wednesday, January 20, 2010


Sheet 47 of 66

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.

1.05Volt +/-5%
Thermal Design Current : 18A
Peack current : 18.059A
OCP MIN : 21.67A







DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.

Title	Selector
-------	----------

LA-5472P

Date: Wednesday, January 20, 2010

Sheet 50 of 66


Rev	A0
-----	----

E2 AC_OK = 17.7V

PR161
TI BQ24745 = 316K
Intersil ISL88731 = 226K
Maxim MAX8731 = 383K



TABLE 3, PIN NAME DIFFERENCES

PIN	MAXIM	INTERSIL
1	GND	NC
3	REF	VREF
4	CCS	ICOMP
5	CCV	NC
6	CCV	VCOMP
7	DAC	NC
8	IINP	ICM
11	VDD	VDDSMB
14	BATSEL	NC
15	FBISA	VFB
16	FBSB	NC
17	CSIN	CSOP
18	CSIP	CSOP
20	DLO	LGATE
21	LDO	VDDP
23	LX	PHASE
24	DHI	UGATE
25	BST	BOOT
"NC" means no-connect		




For Maxim Charger only


Maximum charging current is 6.24A



THIS SHEET OF ENGINEERING DRAWING IS THE PROPRIETARY PROPERTY OF COMPAL ELECTRONICS, INC. AND CONTAINS CONFIDENTIAL AND TRADE SECRET INFORMATION. THIS SHEET MAY NOT BE TRANSFERRED FROM THE CUSTODY OF THE COMPETENT DIVISION OF R&D DEPARTMENT EXCEPT AS AUTHORIZED BY COMPAL ELECTRONICS, INC. NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT PRIOR WRITTEN CONSENT OF COMPAL ELECTRONICS, INC.



GPU_CORE
 Thermal Design Current : 11.587A
 Peak current : 14.990A
 OCP min : 17.988A



	1.0V	0.85V	0.8V	0.75V
GPU_VID_0	0	1	0	1
GPU_VID_1	0	0	1	1

output voltage adjustable network

THIS SHEET OF ENGINEERING DRAWING IS THE PROPRIETARY PROPERTY OF COMPAL ELECTRONICS, INC. AND CONTAINS CONFIDENTIAL AND TRADE SECRET INFORMATION. THIS SHEET MAY NOT BE TRANSFERRED FROM THE CUSTODY OF THE COMPETENT DIVISION OF R&D DEPARTMENT EXCEPT AS AUTHORIZED BY COMPAL ELECTRONICS, INC. NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT PRIOR WRITTEN CONSENT OF COMPAL ELECTRONICS, INC.



DELL CONFIDENTIAL/PROPRIETARY
 Compal Electronics, Inc.
ISL62870 GPU core
 LA-5472P
 Date: Wednesday, January 20, 2010 Sheet 52 of 66

Title	ISL62870 GPU core		
Size	Document Number	Rev	A00




7 PEG_CTX_GRX_P[0..15] >> PEG_CTX_GRX_P[0..15]
7 PEG_CTX_GRX_N[0..15] >> PEG_CTX_GRX_N[0..15]
7 PEG_CRX_GTX_P[0..15] << PEG_CRX_GTX_P[0..15]
7 PEG_CRX_GTX_N[0..15] << PEG_CRX_GTX_N[0..15]

PEG_CRX_GTX_P0	0.1U	0402	10V7K-D	2	1	C1439	PEG_CRX_GTX_C_P0
PEG_CRX_GTX_N0	0.1U	0402	10V7K-D	2	1	C1440	PEG_CRX_GTX_C_N0
PEG_CRX_GTX_P1	0.1U	0402	10V7K-D	2	1	C1441	PEG_CRX_GTX_C_P1
PEG_CRX_GTX_N1	0.1U	0402	10V7K-D	2	1	C1442	PEG_CRX_GTX_C_N1
PEG_CRX_GTX_P2	0.1U	0402	10V7K-D	2	1	C1443	PEG_CRX_GTX_C_P2
PEG_CRX_GTX_N2	0.1U	0402	10V7K-D	2	1	C1444	PEG_CRX_GTX_C_N2
PEG_CRX_GTX_P3	0.1U	0402	10V7K-D	2	1	C1446	PEG_CRX_GTX_C_P3
PEG_CRX_GTX_N3	0.1U	0402	10V7K-D	2	1	C1447	PEG_CRX_GTX_C_N3
PEG_CRX_GTX_P4	0.1U	0402	10V7K-D	2	1	C1448	PEG_CRX_GTX_C_P4
PEG_CRX_GTX_N4	0.1U	0402	10V7K-D	2	1	C1449	PEG_CRX_GTX_C_N4
PEG_CRX_GTX_P5	0.1U	0402	10V7K-D	2	1	C1450	PEG_CRX_GTX_C_P5
PEG_CRX_GTX_N5	0.1U	0402	10V7K-D	2	1	C1451	PEG_CRX_GTX_C_N5
PEG_CRX_GTX_P6	0.1U	0402	10V7K-D	2	1	C1452	PEG_CRX_GTX_C_P6
PEG_CRX_GTX_N6	0.1U	0402	10V7K-D	2	1	C1453	PEG_CRX_GTX_C_N6
PEG_CRX_GTX_P7	0.1U	0402	10V7K-D	2	1	C1454	PEG_CRX_GTX_C_P7
PEG_CRX_GTX_N7	0.1U	0402	10V7K-D	2	1	C1455	PEG_CRX_GTX_C_N7
PEG_CRX_GTX_P8	0.1U	0402	10V7K-D	2	1	C1457	PEG_CRX_GTX_C_P8
PEG_CRX_GTX_N8	0.1U	0402	10V7K-D	2	1	C1458	PEG_CRX_GTX_C_N8
PEG_CRX_GTX_P9	0.1U	0402	10V7K-D	2	1	C1459	PEG_CRX_GTX_C_P9
PEG_CRX_GTX_N9	0.1U	0402	10V7K-D	2	1	C1460	PEG_CRX_GTX_C_N9
PEG_CRX_GTX_P10	0.1U	0402	10V7K-D	2	1	C1461	PEG_CRX_GTX_C_P10
PEG_CRX_GTX_N10	0.1U	0402	10V7K-D	2	1	C1462	PEG_CRX_GTX_C_N10
PEG_CRX_GTX_P11	0.1U	0402	10V7K-D	2	1	C1463	PEG_CRX_GTX_C_P11
PEG_CRX_GTX_N11	0.1U	0402	10V7K-D	2	1	C1464	PEG_CRX_GTX_C_N11
PEG_CRX_GTX_P12	0.1U	0402	10V7K-D	2	1	C1465	PEG_CRX_GTX_C_P12
PEG_CRX_GTX_N12	0.1U	0402	10V7K-D	2	1	C1466	PEG_CRX_GTX_C_N12
PEG_CRX_GTX_P13	0.1U	0402	10V7K-D	2	1	C1468	PEG_CRX_GTX_C_P13
PEG_CRX_GTX_N13	0.1U	0402	10V7K-D	2	1	C1469	PEG_CRX_GTX_C_N13
PEG_CRX_GTX_P14	0.1U	0402	10V7K-D	2	1	C1470	PEG_CRX_GTX_C_P14
PEG_CRX_GTX_N14	0.1U	0402	10V7K-D	2	1	C1471	PEG_CRX_GTX_C_N14
PEG_CRX_GTX_P15	0.1U	0402	10V7K-D	2	1	C1472	PEG_CRX_GTX_C_P15
PEG_CRX_GTX_N15	0.1U	0402	10V7K-D	2	1	C1473	PEG_CRX_GTX_C_N15


Differential signal




Close to GPU




Stuff R1328 for standard I2C ROM.
Stuff R1329 for crypto ROM




PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.



TO DOCKING




TO MB/DOCKING



X7620431001:for Hynix 64Mx16 DDR3 part stuff R1343=15K
X7620431002:For Samsung 64Mx16 DDR3 part stuff R1343=20K

STRAP0	USER[3:0]
STRAP1	3GIO_PADCFG_LUT_ADR[3:0]
STRAP2	PCI_DEVID[3:0]



N10M-NS-S-A2_BGA533-D

Resistor Values	Pull-up to +3V	Pull-down to Gnd
5K	01111	11111
10K	01110	11110
15K	01011	11011
20K	01001	11001
25K	00111	10111
30K	00110	10110
35K	00011	10011
45K	00000	10000

ROM_SCLK	PCIDEVID_EXT, SUB_VENDOR, SLOT_CLK, PEX_PLL_EN
ROM_SI	RAM_CFG[3:0]
ROM_SO	XCLK_417, FB_0_BAR_SIZE, ALT_ADOOR, VGA_DEVICE

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.



LVDS / TMSD

STRAP

GENERAL

SERIAL


Use DP8 and DN8 for GFX thermal monitor



N10M-NS-S-A2_BGA533-D



Compal Electronics, Inc.			
Title			
N10M DP, STRAP, GND			
Size	Document Number	Rev	
	LA-5472P	A00	
Date:	Wednesday, January 20, 2010	Sheet	54 of 66




FBAD[0..63] << FBAD[0..63] 57,58
FBA_CMD[0..30] << FBA_CMD[0..30] 57,58
DQMA#[0..7] << DQMA#[0..7] 57,58
DQSA_RN[0..7] << DQSA_RN[0..7] 57,58
DQSA_WP[0..7] << DQSA_WP[0..7] 57,58




Mode C - Mirror Mode Mapping

DATA Bus		
Address	0..31	32..63
CMD0	CKE_L	
CMD1	A8	A8
CMD2	CS0#_L	
CMD3	A7	A6
CMD4	A2	A1
CMD5	A11	A9
CMD6	A5	A4
CMD7	A0	A12
CMD8	CAS#	CAS#
CMD9	BA1	A3
CMD10	A9	A11
CMD11	CS0#_H	
CMD12	BA0	BA0
CMD13	BA2	A15
CMD14	A3	BA1
CMD15		CS1#_H
CMD16		ODT_H
CMD17	A4	A5
CMD18	A13	A14
CMD19	WE#	A10
CMD20	A1	A2
CMD21	A10	WE#
CMD22	A12	A0
CMD23	CS1#_L	
CMD24	RAS#	RAS#
CMD25	ODT_L	
CMD26	A6	A7
CMD27		CKE_H
CMD28	RST	RST
CMD29	A14	A13
CMD30	A15	BA2

+1.5V_MEM_GFX Source



+1.05V_RUN_VTT_GFX Source



PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.




Compal Electronics, Inc.

Title		
N10M Memory		
Size	Document Number	Rev
	LA-5472P	A00
Date:	Wednesday, January 20, 2010	Sheet 56 of 66

Memory Partition A - Lower 32 bits

FBA_CMD[0..30] << FBA_CMD[0..30] 56.58
FBAD[0..63] << FBAD[0..63] 56.58
DQMA#[0..7] << DQMA#[0..7] 56.58
DQSA_RN[0..7] << DQSA_RN[0..7] 56.58
DQSA_WP[0..7] << DQSA_WP[0..7] 56.58



PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.



Compal Electronics, Inc.

VRAM A Lower


LA-5472P

Date: Wednesday, January 20, 2010

Rev A00

Sheet 57 of 66

Memory Partition A - Upper 32 bits



<u>FBAD[0..63]</u>	<< >>	FBAD[0..63]	56,57
<u>FBA_CMD[0..30]</u>	>>	FBA_CMD[0..30]	56,57
<u>DQMA#[0..7]</u>	>>	DQMA#[0..7]	56,57
<u>DQSA_RN[0..7]</u>	<< >>	DQSA_RN[0..7]	56,57
<u>DQSA_WP[0..7]</u>	<< >>	DQSA_WP[0..7]	56,57

Mode C - Mirror Mode Mapping

Address	DATA Bus	
	0..31	32..63
CMD0	CKE_L	
CMD1	A8	A8
CMD2	CS0#_L	
CMD3	A7	A6
CMD4	A2	A1
CMD5	A11	A9
CMD6	A5	A4
CMD7	A0	A12
CMD8	CAS#	CAS#
CMD9	BA1	A3
CMD10	A9	A11
CMD11		CS0#_H
CMD12	BA0	BA0
CMD13	BA2	A15
CMD14	A3	BA1
CMD15		CS1#_H
CMD16		ODT_H
CMD17	A4	A5
CMD18	A13	A14
CMD19	WE#	A10
CMD20	A1	A2
CMD21	A10	WE#
CMD22	A12	A0
CMD23	CS1#_L	
CMD24	RAS#	RAS#
CMD25	ODT_L	
CMD26	A6	A7
CMD27		CKE_H
CMD28	RST	RST
CMD29	A14	A13
CMD30	A15	BA2

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL") THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.



Compal Electronics, Inc.

Title			
VRAM A Upper			
Size	Document Number	Rev	
	LA-5472P	A00	
Date:	Wednesday, January 20, 2010	Sheet	58 of 66

Version Change List (P. I. R. List)

Item	Page#	Title	Date	Request Owner	Issue Description	Solution Description	Rev.
1	40	HW	7/13/2009	COMPAL	Board ID	R98 change to 130k ohm	X01
2	30	HW	7/13/2009	COMPAL	follow M09 +3.3V_LAN enable control circuit	Depop R47	X01
3	8, 12, 13, 42	HW	7/13/2009	Intel	Intel S3 reduction circuit.	Add R1469, R1497~R1505, R1507~R1509, C1875, C1878~C1884, Q199~Q202, Q205, Q207, Q208, U141, PJP906, PJP907, change R879 to 1.5K, R880 to 750ohm, R624 to 22 ohm, change CPU CDDQ power source from +1.5V_MEM to +1.5V_CPU_VDDQ, change +.075_DDR_VTT discharge gate from RUN_ON_ENABLE# to RUN_ON_CPU1.5VS3#, add +1.5V_CPU_VDDQ discharge circuit, add net "DDR_HVREF_RST_GATE" from U36.A34 to Q119.2, "CPU1.5V_S3_GATE" from U36.A36 to R1501	X01
4	31	HW	7/23/2009	Broadcom	Change C718 value	Change C718 from .47uF to .22uF	X01
5	23	HW	7/23/2009	DELL	Follow DELL request to remove R3P circuit	Delete U140, R136, R138, R156,R507, R516, R519, R529, R531, R534~R536, R594, R1457, R1458, R1462, R1463, C434, C72, C73, C391, C406, pop R142, D2, C219	X01
6	41,37	HW	7/23/2009	Compal	Per M09 lesson learn request	Re-define JTP1, JBI01	X01
7	19	HW	7/23/2009	Intel	GPIO1, 6, 7 need to PU if no used.	Add R1506, R1510	X01
8	40 43	HW	7/23/2009	Compal	Follow SMSC5045 spec	Add R1512, @C1885, C1886, change R560 to 100Kohm, add net name LAT_ON_SW#_R	X01
9	31	HW	7/23/2009	Broadcom	Remove RFID disable circuit	Remove R1062~R1065	X01
10	24	HW	7/23/2009	Compal	CAM Module change from 7 pin to 8 pin	Change pin define for JEDP1	X01
11	31	HW	7/23/2009	Broadcom	R898 and R485 pop at the same time	Depop R898	X01
12	24	HW	7/29/2009	Compal	NVidia BIA_PWM implementation	POP R165, de-pop R166	X01
13	8,15	HW	7/29/2009	Compal	Depop all related components where are located at 0 Z-high area	Depop JXDP1, JXDP2, JDEG1, JP2 connector	X01
14	42	HW	7/29/2009	Compal	For load switches Vout over 5% range concern by power team.	Change Q151 to SIS406D,Q183 to SI7658ADP,Q58 to SI4164DY	X01
15	42	HW	7/29/2009	Compal	Backdrive EA Failure on RAM	Pop R625 and Q79, change R625 to 0603 size.	X01
16	21	HW	7/29/2009	Intel	The PLLs aren't used in a DIS system	De-pop C105 & C106	X01
17	36,39	HW	7/29/2009	DELL	Reconnect the signal UWB_RADIO_DIS#	Connect UWB_RADIO_DIS# from EC5028.A56 to MINI3.20	X01
18	24	HW	7/29/2009	PERICOM	Pericom 8200 SW issue DVI can not work	Add R1516 to pull up U9 pin 23 (P1_OC0) of Pericom 8200 SW with a 4.7K ohm resistor to +3.3_RUN	X01
19	29	HW	7/29/2009	Compal	EMI solution.	Change R1295 to L4 (220ohm) and R1217 from 22ohm to 47ohm.	X01
20	42	HW	7/29/2009	Compal	Base on de-rating report.	Change Q61 from AO4456 to NTMS4107.	X01
21	37, 39	HW	7/29/2009	Compal	GPIO MAP update	Add reserved R1513 between U95.18 and +3.3V_RUN, add R1514 between U95.18 and 5028.A47 named EN_ESATA_RPTR.	X01

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL") THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.



Title			EE P.I.R (1/1)		
Size	Document Number				Rev
	LA-5472P				A00
Date	Wednesday, January 20, 2010		Sheet	59	of 66

DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.

Version Change List (P. I. R. List)

Item	Page#	Title	Date	Request Owner	Issue Description	Solution Description	Rev.
22	31	HW	7/29/2009	Broadcom	Resolve 5882 leakage issue	Add R884, R1515, Q209, Q210	X01
23	31	HW	7/29/2009	Broadcom	Resolve smart cart can't work problem.	pop R775, R537, depop R776.	X01
24	36	HW	7/29/2009	Compal	Change PU power rail for USB_MCARD1_DET#	Change USB_MCARD1_DET# PU power rail to +3.3V_RUN	X01
25	31	HW	7/29/2009	Compal	Remove R1061 to avoid double PU and provide back-drive path.	Remove R1061	X01
26	21	HW	7/29/2009	Compal	Follow the pop option on CRB1.6 to depop C39 for +VCCACLK, C610 for +SATAPLL, C111 and C112 for +1.05V_M_VCCEPW	Depop C610, C39, C111, C112	X01
27	15	HW	7/29/2009	Compal	Base on crystal EA result.	Change external Load Capacitor Value C296 and C297 to 12 pF of Y1.	X01
28	30	HW	7/29/2009	Compal	Base on crystal EA result.	Change external Load Capacitor Value C476 to 33 pF and C427 change to 200 ohm (R808) of Y2.	X01
29	40	HW	7/29/2009	Compal	Base on crystal EA result.	Change external Load Capacitor Value C674 and C675 to 33 pF of Y4.	X01
30	33	HW	7/29/2009	Compal	Base on crystal EA result.	Change external Load Capacitor Value C514 and C515 to 22 pF of X3.	X01
31	29	HW	7/29/2009	Compal	EMI solution.	Change R1215 from 22ohm to 47ohm.	X01
32	29	HW	7/29/2009	Compal	Prevent floating of PCH_GPIO34	Add R1511 10K PD.	X01
33	38	HW	7/29/2009	Compal	Based on DFX team request	Change docking connector from SP030000F0L(JAE_WD2F144WB1_144P-T) to SP030000F0L(JAE_WD2F144WB1R300_144P).	X01
34	36	HW	7/29/2009	Compal	Change PU power rail for PCIE_MCARD3_DET#	Change PCIE_MCARD3_DET# PU power rail to +3.3V_RUN	X01
35	18 35	HW	05/08/2009	Compal	Remove Braidwood circuit.	Delete R1411,R1453,JBW1	X01
36	36	HW	05/08/2009	Compal	Base on SATA EA result, need to trun off Pre-emphasis 0.	Depop R1298,pop R1301.	X01
37	33	HW	10/08/2009	Compal	Base on crystal EA result.	Change C514 C514 to 15pF and R421 to 100 ohm.	X01
38	38	HW	11/08/2009	Compal	Change VGA_ID_DISC & VGA_ID_UMA PU power rail	Change VGA_ID_DISC & VGA_ID_UMA PU power rail from +3.3V_RUN to +3.3V_ALW	X01
39	38	HW	11/08/2009	Compal	Change ODD_DET# PU power rail.	Change ODD_DET# PU power rail to +3.3V_RUN	X01
40	41	HW	11/08/2009	SMSC	Watch dog timer may not be reseted when EMC4002 VDD_PWRGD is not completely at Logic Low.	Add discharge circuit for +3.3V_M	X01
41	23	HW	11/08/2009	SMSC	SMSC review feedback	The pull-up source of the R150 should be changed to +VCC_4002	X01
42	39	HW	11/08/2009	SMSC	per SMSC 5045 AN 19.6, 4002 AN 16.11	R541, R554, R1512 should be 10K.	X01
43	23	HW	11/08/2009	Compal	FAN1_DET# should have 10K PU to +3.3V_M	Add R1517	X01
44	31	HW	11/08/2009	Broadcom	Follow Broadcom request	Delete T159, R494, R498, R631, R634, R898, C640, C641, C642 C647, C1026, L73, add R1522, C1887, C1888, change connection for R496, R497 to GND, change connection for JCS1pin3 and pin4	X01

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL") THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.

DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.

Title EE P.I.R (2/2)

Size Document Number LA-5472P

Date: Wednesday, January 20, 2010 Sheet 60 of 66

Version Change List (P. I. R. List)

Item	Page#	Title	Date	Request Owner	Issue Description	Solution Description	Rev.
45	8	HW	11/08/2009	DELL	Fix the Intel S3 power up timing	Change C1880 from 0.01uF to 0.22uF 0402 cap.	X01
46	31	HW	11/08/2009	Broadcom	Follow Broadcom request	Change C646 to 220nF that was placed near the JSC1 pin 10 (+SC_VCC). And 470nF should be at C718 near U3 (TDA8034)	X01
47	31	HW	12/08/2009	Broadcom	Follow Broadcom request	Change R497 & R496 to 0 ohm, but depop	X01
48	27	HW	12/08/2009	Compal	RGB EA result	C251-C253 to 8.2pF; L61-L63 to 10-Ohm Bead; De-pop C390, C518, C996	X01
49	29	HW	12/08/2009	DELL	Use the SiTimes part due to the cost savings	Change X4 from TXC to SiTimes SIT8102AC3333E12T	X01
50	8	HW	12/08/2009	Intel	Intel review schematic feedback	Add R529 and C1889	X01
51	33	HW	12/08/2009	Richo	Change pop option for R5U242	Change C21 from 10U to 47U, change R46 to C1889 (1uF)	X01
52	31	HW	12/08/2009	Broadcom	BCM5882 pin-C1 "RSTOUT_N" is an open drain I/O type, we need to have 4.7K pull-up to 3.3V_ALW	Add R638	X01
53	30 36	HW	13/08/2009	Compal	Disconnect IO & DOCK VCT	Delete R652 & C41, Rename IO VCT to +LOM_VCT_IO & reserve C712 pad for test.	X01
54	31	HW	13/08/2009	Compal	Broadcom review request	USB_GPIO27 Should have a 0ohm but de-pop resistor.	X01
55	39	HW	14/08/2009	SMSC	SMSC review	Change R561 and R1046 from 1M ohm to 100K ohm.	X01
56	39	HW	14/08/2009	SMSC	SMSC review	Remove R587, base on crystal EA result that only need to change caps value.	X01
57	10	HW	14/08/2009	Intel	Follow Intel recommend to add debug TP.	Add T186~T190	X01
58	31	HW	14/08/2009	Compal	Smart card EA result	Change R772 to 47 Ohm and C1015 to 10pF for resolving SC_CLK Rise/Fail timing issue and also change C633 to 10pF.	X01
59	31	HW	14/08/2009	DELL	Avoid a glitch for DDR_HVREF_RST_GATE, please add a 1.1K 1% no-stuff pull-up to +1.5V_CPU_VDDQ rail on the PM_DRAM_PWRGD_R signal for a back-up option	Change C1889 to 0.1u, add R1518 for PM_DRAM_PWRGD_R but depop.	X01
60	8 45	HW	14/08/2009	DELL	CPU detection since the edge diode has been removed from M'09	Delete T1 and add R1519 for CPU_DETECT# and connect JCPU.AH24 to U36.B18	X01
61	15 19 36	HW	14/08/2009	DELL	Invert the EN_ESATA_RPTR signal and connect this to SATAGP4/GPIO16	Add Q211 and R1520 but depop, pop R1513 and de-pop R1514, change net name from GPIO16 to EN_ESATA_RPTR#	X01
62	34	HW	14/08/2009	Compal	By EMI request, pop common choke	Change Pop option for express card, pop L64, depop R791 R792. For USB2,3 pop L65, L66 and reserve R1524, R1525, R1526 and R1527.	X01
63	30	HW	14/08/2009	Intel	By Intel request	Add R1528 for LAN_REQ#	X01
64	37	HW	17/08/2009	Intel	Adding stitching caps near the DOCK_LOM traces where it crosses over plane splits.	Add C1028	X01

DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.

Title: EE P.I.G (3/3)

Size: Document Number LA-5472P Rev A00

Date: Wednesday, January 20, 2010 Sheet 61 of 66

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL"). THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.

Version Change List (P. I. R. List)

Item	Page#	Title	Date	Request Owner	Issue Description	Solution Description	Rev.
65	38	HW	8/19/2009	NV	Solve DVI issue	Add Q213~Q218,R1523,R1530~R1540	X01
66	26	HW	8/19/2009	Pericom	8200 pin 8,9 add caps to minimize noise	Add C1597 & C1598	X01
67	53	HW	8/19/2009	NV	Reserve crystal for 27M.	Add @R1541,@Y7, @C1891, @C1892	X01
68	24	HW	8/20/2009	Compal	Follow Marguax schematic	Depop R279,R1027	X01
69	53	HW	8/20/2009	Compal	Add PU/PD resistor for 8200 back-up plan	Add R1542~R1544, but depop.	X01
70	35	HW	8/24/2009	Compal	Add PD resistor for back-drive issue	Add R1545~R1547	X01
71	24	HW	8/25/2009	Compal	No need PD/PU resistors at EDP AUX channel	Delete R279 & R1027	X01
72	21	HW	8/25/2009	Compal	Add by pass caps	populate C39 & C610	X01
73	42	HW	8/25/2009	Compal	Un-populate pop option for double discharge path	Un-populate R612,R607 and R1498	X01
74	11	HW	8/25/2009	Compal	Base on power team FDIM test	Change C48,C49,C50,C51,and C52 to 22uF.	X01
75	30	HW	8/26/2009	Intel	Follow Intel WW35 '09	Change R808 to C427 10pF and change C475 to 33pF	X01
76	53	HW	8/27/2009	Compal	Follow Marguax to populate 27MHz crystal for PT build.	Populate Y7,C1891,C1892,R1541 and de-pop R631	X01
77	6,53	HW	9/28/2009	Compal	Populate 27MHz crystal.	Depop R43,R39,R1317, pop R1417	X02
78	17	HW	9/28/2009	Intel	Follow Intel DG 1.62	Change R672 to 1K_0402_5%.	X02
79	15,18	HW	9/28/2009	Compal	Depop XDP circuit component	Depop R118,R94	X02
80	53	HW	9/29/2009	NV	GPU_JTAG_TRST# should be pull down	Pop R1372 and cahnge to 1K 0hm.	X02
81	40	HW	10/20/2009	Compal	Depop R5	Depop R5 for double pull down	X02
82	33	HW	10/20/2009	Compal	Follow DFX recommendation change JSD1 footprint to modify screw hole.	Chnage FOX_2WX131A1-31DD-7F_20P-T to FOX_2WX131A1-31DD-7F_18P.	X02
83	36	HW	10/20/2009	Compal	Correct USB_MCARD2_DET# PU power rail	Chnage power rail from +3.3V_RUN to +3.3V_ALW_PCH	X02
84	17	HW	10/20/2009	Compal	Follow schematic check list 2.0, change resistor value	Chnage R268 from 1K to 10K	X02
85	16	HW	10/20/2009	Compal	Change R910 value and placement	Change R910 form 0 ohm to 22 ohm and place near PCH side.	X02
86	37	HW	10/26/2009	Compal	Chnage USB common choke by EMI request	Change L95 L96 from DLW21SN900SQ2_0805~D to HCMC0805-900MFS_4P~D	X02
87	23	HW	10/26/2009	Compal	Change OTP temperature	change R151 from 953ohm to 1.02Kohm	X02
88	53	HW	10/27/2009	Compal	To solve 27 Mhz noise issue	Connect Y7 pin 2 and 4 to GND.	X02
89	31	HW	10/27/2009	Broadcom	For 5882-B0 request	L71, L72 68nH, 2%, 400mA; C1070, C1071 1500pF, 2%, 50V; C1886, C1887 150pF, 2%, 50V	X02
90	15	HW	10/29/2009	Compal	Change flash ROM part number	Due to W25X32VSSIG will be EOL, change part number to W25Q32BVSSIG.	X02

DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.



Title			Rev A00
EE P.I.G (4/4)			
Size	Document Number	LA-5472P	
Date:	Wednesday, January 20, 2010	Sheet	62 of 66

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL") THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.

Version Change List (P. I. R. List)

Item	Page#	Title	Date	Request Owner	Issue Description	Solution Description	Rev.
91	16	HW	10/29/2009	Dell	MEM SMBus design needs to change	Move Q190 connection, add R1549,R1550, add net name DDR_XDP_CLK/DAT	X02
92	29	HW	10/29/2009	Compal	Create a low pass filter with the pole set at 36kHz to filter out of band noise	De-pop C1066 & C1067, R1090, R1089 ; R340 & R342, R1091 & R1092 change to 2k, add C1893-C1896 1000pF.	X02
93	40	HW	11/02/2009	Compal	Change BID	Change R98 form 130K ohm to 33K ohm.	X02
94	8,15	HW	11/02/2009	Compal	To avoid stub for SM bus EA quality XDP is not use.	Add R1551~R1556 but depop	X02
95	36	HW	11/02/2009	DELL	Support WiMax LED status	Need to populate R840	X02
96	43	HW	11/05/2009	Compal	To avoid golden finger was scraped on FFC.	Change sniffer connector from TYCO_1-1734820-2 to TYCO_1-2041070-2.	X02
97	41	HW	11/05/2009	Compal	Chnage TP SMBus PU power rail.	Change power rail from +5V_ALW to +3.3V_ALW	X02
98	31	HW	11/05/2009	BRCM	Delete 2nd ROM for BRCN5982	By BRCM review result ,delete U14.	X02
99	24	HW	11/10/2009	Compal	LCD power sequencing issue	change R161 from 470 to 100 ohm .	X02
100	19	HW	11/11/2009	DELL	PCH driving the siganl low at GPIO15 initial.	Add R1557 2.2K PU resistor to +3.3V_ALW_PCH on the SIO_EXT_WAKE# signal.	X02
101	15	HW	11/11/2009	DELL	To change the pin on the EC side to OD and add a pull-up to PCH's core well	Add R1558 10K PU resistor to +3.3V_RUN on the ME_FWP signal.	X02
102	15,40	HW	11/11/2009	Compal	RTC timing issue	Y1 & Y4 change from 1TJS125DJ4A420P to Q13MC30610018. Opreating temperature should -40~+85 degree to meet test requirement.	X02
103	19	HW	11/17/2009	Compal	Chnage GPIO34 of PCH from PD to PU	Change from PD to PU +3.3V_RUN	X02
104	31	HW	11/17/2009	Compal	Follow Marguax schmatic and it also could pass smart card EA.	To change R772 from 47 ohm to 22 ohm	X02
105	31	HW	11/17/2009	Compal	To solve touch pad ESD issue	Change L41 and L42 to 100 ohm (R1564 & R1565)	X02
106	15	HW	11/19/2009	Compal	Follow Intel check list rev2.0	Change R2244 to tolerance from 5% to 1%	X02
107	15	HW	11/19/2009	Compal	Follow DCU 414044 Rev2.0	Depop R123 ,R804-R807 and R1281,R1282 R1315.	X02
108	38	HW	12/22/2009	Compal	Simplo battery slice EMI issue	Add C1897 and C1898(Depop, reserve for EMI test)	A00
109	37	HW	12/22/2009	Compal	DFB issue ,finger printer connector will easy shift during reflow process.	Change finger printer connector from TYCO_1734242-6_6P-T to TYCO_2041070-6_6P-T	A00
110	31	HW	12/22/2009	Compal	By Broadcom recommend	Change L71,L72 from 68nH to 150nH, C1070,C1071 from 1500pF to 390pF.C1887,C1888 from 150pF to 390pF.	A00
111	32	HW	12/22/2009	Compal	Change TCM to T1 version	Change TCM from SSX44B-D-T to SSX44-D-T1	A00
112	40	HW	12/22/2009	Compal	Change BID	Change R98 form 33K ohm to 1K ohm.	A00
113	08	HW	12/22/2009	Compal	Depop CPU XDP and JTAG circuit for for production systems	Depop C19,C20,R6,R68,R19,R7,R3, R780~R785,R22,R24,R1153,R1156,R66,R1241,R1257	A00
114	15	HW	12/22/2009	Compal	Depop PCH JTAG circuit for for production systems	Depop R123, R804-R807,R1281,R1282,R1315	A00

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL") THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.

DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.

EE P.I.G (5/5)

Date: Wednesday, January 20, 2010
Sheet 63 of 66

Version Change List (P. I. R. List)

Item	Page#	Title	Date	Request Owner	Issue Description	Solution Description	Rev.
------	-------	-------	------	------------------	-------------------	----------------------	------

115	33, 34	HW	01/07/2010	Compal	Change R5U2542 form ES2 to ES3	Change part number from SA00003C21L to SA00003C22L	A00
116	27	HW	01/14/2010	Compal	RGB EMI issue	Change L61,L62,L63 from 10nH to 27nH, C251,C252,C253 from 8.2pF to 2pF and pop C390,C518,C996	A00
117	37	HW	01/15/2010	Compal	Change SATA repeater part to power saving part	Change U95 to SA00003P10L	A00
118	26	HW	01/19/2010	Pericom	Pericom DP SW DP8200 has new silicon W version in stead of Y version	Change U9 to SA00003CD2L	A00

PROPRIETARY NOTE: THIS SHEET OF ENGINEERING DRAWING AND SPECIFICATIONS CONTAINS CONFIDENTIAL TRADE SECRET AND OTHER PROPRIETARY INFORMATION OF DELL INC. ("DELL") THIS DOCUMENT MAY NOT BE TRANSFERRED OR COPIED WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF DELL. IN ADDITION, NEITHER THIS SHEET NOR THE INFORMATION IT CONTAINS MAY BE USED BY OR DISCLOSED TO ANY THIRD PARTY WITHOUT DELL'S EXPRESS WRITTEN CONSENT.



DELL CONFIDENTIAL/PROPRIETARY

Compal Electronics, Inc.

Title

EE P.I.G (6/6)

Size Document Number

LA-5472P

Date: Wednesday, January 20, 2010

Rev A00

Sheet 64 of 66

Version Change List (P. I. R. List)

Item	Page#	Title	Date	Request Owner	Issue Description	Solution Description	Rev.
1	50	Selector	7/20	TI	CSS GC logic wrong issue	Add PR282 180_ohm to GND	X01
2	46	1.5V_MEM	7/20	Compal ADC Guangyong	Add droop resistor for TI solution	Add PR77	X01
3	45	+3.3V/+5V	8/17	Compal ADC Guangyong	Change 3V/5V choke for cost down	change PL5 from SH00000H90L to SH00000FN0L change PL6 from SH00000HB0L to SH00000HR0L	X01
4	50	Selector	8/17	Compal	Add 1M_ohm pull down to fix ACAV_IN_NB oscillation when battery mode S5	Add PR283	X01
5	50	Selector	8/17	TI	new version CD3301 (PG2.1) don't need PD22 and PR282	depop PD22 add PR282, pop PR430	X01
6	50	Selector	8/17	TI	DOCK_AC_OFF_EC floating issue	add PR285	X01
7	52	ISL62872_GPU	8/17	Dell / intersil	change PU901 to ISL62872 to support NV VID fixture	change PU901 to ISL62872 from ISL62870 and support circuit.	X01
8	49	+VCORE MAX17030	8/17	Compal	change thermistor package from 0603 to 0402 for cost down	Change PH3,PH4 and PH5 from SL200000B0L to SL200000W0L	X01
9	47	1.8V_RUN	8/18	MAXIM	Output ripple voltage unstable issue	Change PC314 from SE00000868L(22u/0805) to SE00000000L(100u/1206) Change PR409 from SD03480618L (8.06k) to SD03460418L (6.04k) Change PR410 from SD03440218L(4.02k) to SD03430118L(3.01k) Change PR408 from SD014402A8L(40.2 Ohm) to SD0000008H8L(51 Ohm) Change PC315 from SE000003W8L(820pF) to SE076333K8L (3300pF) Change PR411from SD00000268L(6.98K) to SD03445318L(4.53K) Change PC310 from SE074102K8L(1000P) to SE074472K8L(4700pF) Change PC309 from SE071330J8L (33pF) to SE071560J8L (56pF) Change PC311 from SE042104K8L(.1u/0603/25V) to SE076104K8L(.1u/0402/16V) Add PR413 SD02800008L (0 Ohm) Change PR102, PR103 and PR104 from SD013220B8L(2.2) to SD00000V98L(1.1) Change PR310, PR311 and PR312 from SD03430118L(3.01k) to SD03424918L(2.49k) Change PR307, PR308 and PR309 from SD03422118L(2.21k) to SD03417418L(1.74k) Change PR137 from SD03449910L(4.99k) to SD03447518L(4.75k) Add PC271,PC272 and PC273 SE075223K8L(0.022uF)	X01
10	49	+VCORE MAX17030	8/20	Maxim	Vcore FDIM issue	Change PR188 and PR201 from SD03451018L(5.1k) to SD00000U28L (4.3k) Change PR199 and PR203 from SD03416228L(16.2k) to SD03413728L(13.7k) Change PR198 from SD03468008L(680 Ohm) to SD03418008L(180 Ohm) Change PR202 from SD03468008L(680 Ohm) to SD03410008L(100 Ohm) Change PC108 and PC116 from SE074331K8L(330p) to SE074471K8L(470p) Change PR200 from SD00000DM0L(200k) to SD03451028L(51k) Change PC115 from SE071300J0L(SE071300J0L) to SE071220J8L(22P) Change PC106 from SE071300J0L(30P) to SE071330J8L(33P) Change PR204 from SD03447518L(4.75K) to SD03452318L(5.23K) Change PR205 from SD03444228L(44.2K) to SD03424028L(24K) Change PR207 from SD00000LZ0L(3.83K) to SD00000J20L(4.32K) Change PR208 from SD03482518L(8.25k) to SD03464918L(6.49k)	X01
11	48	+1.05VM/ +1.05VTT	8/20	ON	Fine tune DC accurcay	Change PU301 from SA00003B10L(MAX15050) to SA00003CG0L (ISL8014) and support circuit	X01
12	47	1.8V_RUN	8/25	DELL	1.8V transient 0.1A ~ 1.6A output voltage over spec		

Version Change List (P. I. R. List)

Item	Page#	Title	Date	Request Owner	Issue Description	Solution Description	Rev.
13	49	Vcore	8/25	MAXIM	Improve DC accuracy	Change exposed pad to PGND from AGND	X01
14	49	Vcore	8/25	MAXIM	Vender recommend PSI# pull down 10k	Change PR334 from SD03410018L (1k) to SD02810028L(10k)	X01
15	51	Charger	8/25	Compal ADC Guangyong	Improve charger choke saturation current at 100 degree C	Change PL14 from SH04856AM8L (5.6u) to SH00000I60L (5.6u)	X01
16	44	DCIN	8/25	Compal	3.3V_ALW2 black driver issue with RTC battery only	Change PD1 from SC100000Q0L(BAT54CW) to SCSB715F08L (RB715F)	X01
17	49	Vcore	8/27	Compal	Reseve resistor pad for debug	Add PR122 and PR123	X01
18	52	GPU_Core	9/01	Intersil	PR916 and PR911 for debug change to 0 Ohm	Change PR916 from SD02810018L(1K) to SD02800008L(0 Ohm) Change PR911 from SD02810018L(1K) to SD02800008L(0 Ohm)	X01
19	49	Vcore	9/01	MAXIM	Fine tune Imon time constant meet Intel SPEC 300uS~500uS	Change PC270 from SE075223K8L (0.022U) to SE076333K8L (.033U)	X01
20	49	Vcore	9/01	MAXIM	Make sure DPRSLPVE low level under 0.33V	Change PR109 from SD03449908L (499 Ohm) to SD02800008L (0 Ohm)	X01
21	52	GPU_Core	10/06	NV	GPU_CORE default setting should be 1V for faster to boot to system and short warm up time for GPU	Depop PR910 and POP PR927	X02
22	44	DC_IN	10/13	TI	High inrush current on DC_IN when AC adapter plug in	Change PR20 from SD02800008L(0 Ohm) to SD02810028L(10k)	X02
23	49	Vcore	10/20	MAXIM	3 phase overlap issue with 2nd source MOSFET	Add PC198, PC199, PC255, PC256, PC259 and PC260 SE074122K8L (1200pF)	X02
24	48	+1.05VTT	10/28	INTEL	Fine tune H_VTTPWRGD voltage level meet Vih(min) = 0.75 * Vtt	Change PR94 from SD03410028L (10k) to SD03427418L (2.74K) Change PR93 from SD03428728L (28.7k) to SD03493118L (9.31K)	X02
25	49	+VCORE	11/03	Compal	change thermistor package from 0603 to 0402 for cost down	Change PH1 from SL20000068L (100K 0603) to SL20000160L (100K 0402)	X02
26	52	GPU_Core	11/12	Compal	For NVIDIA output voltage +/- 30mV criteria	Change PC918 from SGA19331D1L (330u/9m Ohm) to SGA0000420L (470u/4.5m Ohm)	X02
27	48	+1.05VTT/ +1.05VM	11/16	ON	Bost diode over stress	Change PD19 and PD27 from SC1B751V08L(RB751V) to SCS00003M0L(BAT54HT1)	X02
28	51	Charger	01/12	Compal	Reduce Pin33,34 and 35 of the CD3301 surge current	Change PC351 from SE00000130L (1u/0805) to SE043104M8L (0.1u/0805) Change PR404 from SD02800008L (0 Ohm) to SD028100B8L (1 Ohm)	A00